

## **PRODUCT SPECIFICATION SHEET**

Item Name : Texuede 1000

### Specifications :

- Contents: 80% polyester, 15% cotton, 5% polyurethane
- Width: 54"
- Nominal weight : App. 11 oz/square yard
- Repeat: N/A
- Roll Length: App. 50yds

### General Characteristics :

- Superior wear resistance: Exceeds 60,000 rubs (ASTM D4157 Wyzenbeek)
- Colorfastness to light (AATCC-16/passes)
- Colorfastness to crocking (AATCC-8/passes)
- Tensile strength (ASTM D5034)
- Tear strength (ASTM D1424)
- Seam slippage (ASTM D4034)

### Flammability\* :

- FMVSS-302
- CA Bulletin 117 – Class A
- UFAC/NFPA-260 Class 1

\*This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

### Care & Cleaning :

- Texuede 1000 contains built-in stain resistant system. Liquid stains and spills will remain on the surface temporarily, but should be cleaned as soon as possible.
- Stain Removal: Spot clean with mild soap and warm water solution. Rinse the cleaned area with clean/clear water and dry with air or lint-free cloth

Warranty : Please refer to our Terms of Sales for warranty information.